

## Specification (typical values)

### PHYSICAL PROPERTIES

Core material	High density recycled post industrial PU foam
Density (kg/m <sup>3</sup> )	105
Top surface	Printed stabilising non-woven fleece bonded by blue film
Bottom surface	Stabilising non-woven fleece bonded by blue film
Nominal thickness (mm)	10.00
Dimensions (m <sup>2</sup> )	1.37m x 11.00m = 15.07
Roll weight (kg)	15.70

PRODUCT PERFORMANCE - BS EN 14499	RESULTS	STANDARD
Elongation at 30N - length / width (%)	<7.5 / <12.5	BS EN ISO 13934-1
Breaking strength - length / width (N)	>80.0 / >50.0	
Loss in thickness after long term static loading (%)	<2.5	ISO 3416
Loss in thickness after dynamic loading (%)	<5.0	BS ISO 2094
Work of compression after dynamic loading (J/m <sup>2</sup> )	>160	BS 4098 / BS ISO 2094
Retained work of compression (%)	>70	
Compression after dynamic loading (mm)	7.0	
Resistance to cracking	Pass	BS EN 14499
Assessment of wear	No negative effect	BS ISO 1036

### OTHER RELEVANT DATA

<b>Flammability</b>		
Hot metal nut test	Pass - Medium radius of effect	BS 4790 / BS 5287
<b>Thermal performance</b>		
Thermal resistance (tog)	2.51	BS 4745
<b>Acoustic performance</b>		
Impact sound reduction (dB)	44	BS EN ISO 10140-3
<b>USAGE CLASSIFICATION</b>	L/U	Luxury Use



Floorwise reference: F9PA/Issue 2/July 2023

Notes:

1. All values are nominal and may vary within our manufacturing tolerances
2. Some values may have been derived from the testing of similar products

**10**mm

Comfort ★★★★★ Durability ★★★★★ Bouncebackability ★★★★★