

Specification (typical values)

PHYSICAL PROPERTIES

Core material	Recycled crumb rubber
Density (g/m ³)	3600
Top surface	Soft needled felt
Bottom surface	Recycled crumb rubber
Nominal thickness (mm)	11.00
Dimensions (m ²)	1.37m x 7.30m = 10.00
Roll weight (kg)	36.00

PRODUCT PERFORMANCE - BS EN 14499	RESULTS	STANDARD
Elongation at 30N - length / width (%)	<7.5 / <5.0	BS EN ISO 13934-1
Breaking strength - length / width (N)	>230.0 / >340.0	
Loss in thickness after long term static loading (%)	<17.5	ISO 3416
Loss in thickness after dynamic loading (%)	<10.0	BS ISO 2094
Work of compression after dynamic loading (J/m ²)	>140	
Retained work of compression (%)	>80	BS 4098 / BS ISO 2094
Compression after dynamic loading (mm)	5.0	
Resistance to cracking	Pass	BS EN 14499
Assessment of wear	No negative effect	BS ISO 1036

OTHER RELEVANT DATA

Flammability		
Hot metal nut test	Pass - Low radius of effect	BS 4790 / BS 5287
Thermal performance		
Thermal resistance (tog)	2.55	BS 4745
Acoustic performance		
Impact sound reduction (dB)	34	BS EN ISO 10140-3
USAGE CLASSIFICATION	L/U	Luxury Use



Floorwise reference: F9FTDPR/Issue 3/July 2023

Notes:

1. All values are nominal and may vary within our manufacturing tolerances
2. Some values may have been derived from the testing of similar products

11 mm

Comfort ★★★★★☆☆ Durability ★★★★★★★ Bouncebackability ★★★★★★★